

Ruby - Feature #1031

-U ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ ☐ **--help** ☐ ☐ ☐

01/21/2009 07:02 PM - sakuro (Sakuro OZAWA)

Status:	Rejected	
Priority:	Normal	
Assignee:	matz (Yukihiro Matsumoto)	
Target version:	2.0.0	
Description =begin irb -U Same as ruby -U -U ruby -U . ? \$ ruby19 --version ruby 1.9.1p0 (2009-01-20 revision 21700) [i386-darwin9.6.0] \$ ruby19 --help Usage: ruby19 [switches] [--] [programfile] [arguments] -T[level] turn on tainting checks -v print version number, then turn on verbose mode =end		

History

#1 - 01/21/2009 08:19 PM - shyouhei (Shyouhei Urabe)

- Status changed from Open to Rejected

```
=begin
man
=end
```

#2 - 01/21/2009 08:55 PM - akira (akira yamada)

=begin

On 2009/01/21, at 20:18, Shyouhei Urabe wrote:

[illegible]

<http://redmine.ruby-lang.org/issues/show/1031>

```
manpage[0][0][0][0]--help[0][0][0][0][0][0][0][0][0][0]
[0][0][0][0][0][0]?
```

```
=end
```

#3 - 01/21/2009 10:59 PM - naruse (Yui NARUSE)

```
=begin  
ruby --help ██████████  
██████████  
██████████ --help ██████████  
=end
```

#4 - 01/22/2009 01:56 PM - duerst (Martin Dürst)

```
=begin
1#####
##### 24x80 #####
##### --help #####
```

[illegible]

=end

#9 - 10/11/2009 01:16 AM - naruse (Yui NARUSE)

```
=begin
#####
##### Developer #####
=end
```

#10 - 03/25/2010 01:45 AM - mame (Yusuke Endoh)

```
=begin
#####

In message "Re: \[ruby-dev:37818\] [Bug #1031] -U ##### --help ""
on Thu, 22 Jan 2009 14:02:11 +0900, Shyouhei Urabe redmine@ruby-lang.org writes:

|24#####80#####
|#####1#####assign#####

#####
ruby-core#####
```

```
#####

24#####80#####
##### 24 #####

$ ./ruby -h | wc -l
24

#####

--
Yusuke Endoh mame@tsg.ne.jp
=end
```

#11 - 03/25/2010 01:45 PM - shugo (Shugo Maeda)

```
=begin
#####

20100325 1:45 Yusuke Endoh redmine@ruby-lang.org:

|24#####80#####
|##### 24 #####

$ ./ruby -h | wc -l
24

#####

#####24#####80x24
#####
lessiv23#####

--
Shugo Maeda

=end
```

#12 - 03/25/2010 03:12 PM - shyouhei (Shyouhei Urabe)

```
=begin
#####
#####79#####22#####

Usage:
ruby [options ...] -- script [script options...]

Options:
```

Please consult the online manual for the comprehensive list of options understood, but the most frequently used ones are:

-O[n]	much like perl -O
-a	much like perl -a
-c	much like perl -c
-d	muck like perl -d
-e program	much like perl -e
-F pattern	much like perl -F
-i[ext]	much like perl -i
-I dir	much like perl -I
-l	much like perl -l
-n	much like perl -n
-p	much like perl -p
-r lib	pre-require lib before running the script
-T level	much like perl -T, but several levels are there.
-v	much like perl -v
-w	much like perl -w

Attachment: signature.asc
=end

#13 - 03/25/2010 08:25 PM - shugo (Shugo Maeda)

=begin
~~~~~

2010032515:11 Urabe Shyouhei [shyouhei@ruby-lang.org](mailto:shyouhei@ruby-lang.org):

~~~~~  
~~~~~79000220000

~~~~~perl -h~~~~~perl0000240000000000  
~~~~~24000000000000000000

--  
Shugo Maeda  
  
=end

#14 - 04/14/2010 01:11 AM - mame (Yusuke Endoh)

=begin  
~~~~~

~~~~~ .....

2010032515:11 Urabe Shyouhei [shyouhei@ruby-lang.org](mailto:shyouhei@ruby-lang.org):

~~~~~

ruby -h ~~~~~
~~~~~  
~~~~~  
~~~~~

○~~~~~

- 1 : -e -l -r -v (-h)
- 2 : -d -T -w -W
- 3 : -E (-U)

○~~~~~

- 1 : -l -n -p
- 2 : -O -a -F -i

~~~~~

- ruby -h ~ -c -s -S -x --version ~~~~~
- -U ~~~~~

```

--copyright
LEGAL
)

```

```

diff --git a/ruby.c b/ruby.c
index 5c1eef0..2a36cb6 100644

```

```
--- a/ruby.c
```

```
+++ b/ruby.c
```

```
@@ -135,7 +135,6 @@ usage(const char *name)
```

```
static const char *const usage_msg[] = {
```

```
"-0[octal]    specify record separator (\0, if no argument)",
```

```
"-a          autosplit mode with -n or -p (splits $_ into $F)",
```

- "-c check syntax only",
- "-Cdirectory cd to directory, before executing your script",
- "-d set debugging flags (set \$DEBUG to true)",
- "-e 'command' one line of script. Several -e's allowed. Omit [programfile]",
- @@ -147,13 +146,11 @@ usage(const char *name)
- "-n assume 'while gets(); ... end' loop around your script",
- "-p assume loop like -n but print line also like sed",
- "-rlibrary require the library, before executing your script",
- "-s enable some switch parsing for switches after script name",
- "-S look for the script using PATH environment variable",
- "-T[level=1] turn on tainting checks",
- "-U set internal character encoding as UTF-8",
- "-v print version number, then turn on verbose mode",
- "-w turn warnings on for your script",
- "-W[level=2] set warning level; 0=silence, 1=medium, 2=verbose",
- "-x[directory] strip off text before #!ruby line and perhaps cd to directory",
- "--copyright print the copyright",
- "--version print the version",
- NULL

```

--long-help

```

```
--
```

```
Yusuke ENDOH mame@tsg.ne.jp
```

```
=end
```

#15 - 05/10/2010 11:38 PM - mame (Yusuke Endoh)

- Priority changed from Normal to 3

```
=begin
```

```
=end
```

#16 - 07/17/2010 03:33 PM - yugui (Yuki Sonoda)

- Target version changed from 1.9.2 to 2.0.0

```
=begin
```

```
=end
```

#17 - 06/11/2011 02:17 PM - ko1 (Koichi Sasada)

```


```

#18 - 06/24/2011 12:12 AM - naruse (Yui NARUSE)

- Tracker changed from Bug to Feature

```

Feature

```

#19 - 02/08/2012 03:21 AM - kosaki (Motohiro KOSAKI)

- Status changed from Assigned to Rejected

```


```

Files

ruby.c.diff	622 Bytes	01/21/2009	sakuro (Sakuro OZAWA)
-------------	-----------	------------	-----------------------