

Ruby - Bug #12426

Error when compiling win32ole.c on cygwin

05/24/2016 11:28 PM - duerst (Martin Dürst)

Status:	Closed	
Priority:	Normal	
Assignee:	nobu (Nobuyoshi Nakada)	
Target version:		
ruby -v:	ruby 2.4.0dev (2016-05-24 trunk 55139) [x86_64-cygwin]	Backport: 2.1: DONTNEED, 2.2: DONTNEED, 2.3: DONTNEED
Description I get the following error when compiling ruby on cygwin: <pre>compiling win32ole.c In file included from win32ole.h:3:0, from win32ole.c:18: win32ole.c: In function 'fole_initialize': ../../../../include/ruby/ruby.h:2224:36: error: call to 'rb_scan_args_bad_format' declared with attribute error: bad scan arg format /(rb_scan_args_valid_p(fmt) rb_scan_args_bad_format(fmt)) \ ^ ../../../../include/ruby/ruby.h:2236:8: note: in expansion of macro 'rb_scan_args_verify' rb_scan_args_verify(fmt, varc), vars) ^ ../../../../include/ruby/ruby.h:2156:9: note: in expansion of macro 'rb_scan_args0' rb_scan_args0(argc,argv,fmt,(sizeof((VALUE*[]){__VA_ARGS__})/sizeof(VALUE*)),((VALUE*[]){__VA_ARGS__})), \ ^ win32ole.c:2448:5: note: in expansion of macro 'rb_scan_args' rb_scan_args(argc, argv, "l*", &svr_name, &host, &others); ^ win32ole.c: At top level: cc1: warning: unrecognized command line option '-Wno-self-assign' cc1: warning: unrecognized command line option '-Wno-constant-logical-operand' cc1: warning: unrecognized command line option '-Wno-parentheses-equality' cc1: warning: unrecognized command line option '-Wno-tautological-compare' Makefile:256: recipe for target 'win32ole.o' failed make[2]: *** [win32ole.o] Error 1 make[2]: Leaving directory '/cygdrive/c/Data/ruby/ext/win32ole' exts.mk:259: recipe for target 'ext/win32ole/all' failed make[1]: *** [ext/win32ole/all] Error 2 make[1]: Leaving directory '/cygdrive/c/Data/ruby' uncommon.mk:204: recipe for target 'build-ext' failed make: *** [build-ext] Error 2</pre>		

Associated revisions

Revision c7bc778ddea75a3608b911c5412030171590466a - 05/25/2016 08:11 AM - nobu (Nobuyoshi Nakada)

ruby.h: rb_scan_args_validate

- include/ruby/ruby.h (rb_scan_args_validate): move failed condition to the terminal. [ruby-core:75714] [Bug #12426]

git-svn-id: svn+ssh://ci.ruby-lang.org/ruby/trunk@55158 b2dd03c8-39d4-4d8f-98ff-823fe69b080e

Revision c7bc778d - 05/25/2016 08:11 AM - nobu (Nobuyoshi Nakada)

ruby.h: rb_scan_args_validate

- include/ruby/ruby.h (rb_scan_args_validate): move failed condition to the terminal. [ruby-core:75714] [Bug #12426]

git-svn-id: svn+ssh://ci.ruby-lang.org/ruby/trunk@55158 b2dd03c8-39d4-4d8f-98ff-823fe69b080e

History

#1 - 05/25/2016 08:11 AM - nobu (Nobuyoshi Nakada)

- Status changed from Open to Closed

Applied in changeset r55158.

ruby.h: rb_scan_args_validate

- include/ruby/ruby.h (rb_scan_args_validate): move failed condition to the terminal. [\[ruby-core:75714\]](#) [Bug [#12426](#)]

#2 - 06/08/2016 05:35 AM - usa (Usaku NAKAMURA)

- Backport changed from 2.1: UNKNOWN, 2.2: UNKNOWN, 2.3: UNKNOWN to 2.1: DONTNEED, 2.2: DONTNEED, 2.3: DONTNEED